

CARRABILITÀ



CARRIABILI

EROGATORI MOBILI CARRIABILI
POLYETHYLENE TANK FOR FUEL TRANSPORT
ADR Approved

EASY
980



EASY
600



EASY
440



CARRY
440



CARRY
220



EASY
210



CONFIG. EROGAZIONE FUEL DISPENSERS

PERSONALIZZA IL TUO CARRIABILE

***600/980 LT** omologati ADR -
220/440 lt in esenzione ADR
CUSTOMIZE YOUR TANK - 600/980
LT ADR APPROVED - 220/440 LT
ADR EXEMPTION

BASIC + pompa 40 lt/min 12 V/24V

+ tubo 4 m

210-440 + pistola automatica
600-980 + contalitri K24



PREMIUM + pompa 40 lt/min 12 V/24V

+ arrotolatore tubo 8 m DN25

+ pistola automatica

980 + contalitri digitale/analogico



ECO + pompa 40 lt/min 12 V/24V

+ tubo 4 m

220 + pistola automatica

440 + contalitri digitale

+ filtro impurità



IT.

Serbatoi trasportabili rigidi in polietilene. Adatte ad ogni tipo di esigenza, le cisterne in polietilene rigido sono complete di gruppo di erogazione e contalitri, il filtro impurità è opzionale, permettono di effettuare le operazioni di rifornimento dei mezzi d'opera dove necessario, consentendo un notevole risparmio di tempo. Il gruppo di erogazione, posto sulla parte superiore, è chiuso all'interno da un robusto coperchio di protezione realizzato in vetroresina che garantisce una perfetta protezione del gruppo pompa e dei dispositivi di sicurezza. Sono disponibili in 4 diverse capacità: 220 e 440 litri omologati adr 600 litri e 980 litri. In quest'ultimi modelli di produzione tedesca (cemo) è possibile installare un sistema di batterie al litio che permette di operare in modo indipendente dal collegarsi con i cavi alle batterie del mezzo da rifornire.

CERTIFICATI A CORREDO

- certificato di collaudo
- tabella centimetrica di taratura

DOTAZIONE

- Pistola di erogazione a blocco automatico;
- Supporto porta pistola integrato;
- MT. 4 tubo di erogazione flessibile;
- Valvola di aerazione integrata;
- Tasche per presa muletto;
- Impugnatura per il sollevamento a vuoto;
- Eletropompa da 40 lt./min.- 12V o 24V;
- Cavo elettrico di alimentazione con pinze per collegamento diretto alla batteria;

OPTIONAL • Contalitri modello K 24 a turbina con display digitale;

- LI-ION battery system - batterie ricaricabili 12V estraibili.

COMBI + pompa 40 lt/min 12 V/24V
850DIESEL + arrotolatore tubo 8 m DN25
+ pistola automatica
+ contalitri digitale/analogico
+ filtro acqua



BATTERY

210-440
600



CARATTERISTICHE TECNICHE TECHNICAL FEATURES

EN.

Rigid transportable polyethylene tanks. Suitable for any type of need, the rigid polyethylene tanks are complete with dispensing unit and liter-counter, the impurity filter is optional, they allow to carry out the refueling operations of the work vehicles where necessary, allowing a considerable saving of time. The dispensing unit, located on the upper part, is closed inside by a robust protective cover made of fiberglass which guarantees perfect protection of the pump unit and safety devices. They are available in 4 different capacities: 220 and 440 liters approved for 600 liters and 980 liters. In the latter German production models (cemo) it is possible to install a lithium battery system that allows you to operate independently from connecting with cables to the batteries of the vehicle to be refueled.

DOCUMENTS AND CERTIFICATES

- test certificate
- calibration centimeter table

SUPPLIED

- Automatic block dispensing gun;
- Integrated gun holder support;
- MT. 4 flexible dispensing tube;
- Integrated ventilation valve;
- Pockets for forklift truck grip;
- Handle for vacuum lifting;
- 40 lt./min.- 12V or 24V electric pump;
- Electric power cable with pliers for direct connection to the battery;

OPTIONAL • Turbine flow meter model K 24 with digital display;

- LI-ION battery system - 12V removable rechargeable batteries.

ACCESSORI ACCESSORIES

BACINO DI CONTENIMENTO 100% PER USO A TERRA

BASIN 110% FOR GROUND USE



MODELLO MODEL	VOLUME lt	PESO kg		MATERIALE MATERIAL	ESENZIONE ADR ADR APPROVED	BACINO 110 % PER USO A TERRA BASIN 110% FOR GROUND USE
			mm			
EASY 210	210	22	785 X 595 X h: 685	polyethylene	SI/YES	OPTIONAL
CARRY 220	220	37	630 x 830 x h: 715	polyethylene	SI/YES	OPTIONAL
EASY 440	440	35	1180 x 80 x h: 710	polyethylene	SI/YES	OPTIONAL
CARRY 440	440	55	1220 x 830 x h: 810	polyethylene	SI/YES	OPTIONAL
EASY 600	600	66	1160 x 800 x h: 1100	polyethylene	SI/YES	OPTIONAL
EASY 980	980	130	1300 x 1100 x h: 1150	polyethylene	SI/YES	OPTIONAL
COMBI 980	850+100	121	1300 x 1100 x h: 1150	polyethylene	SI/YES	OPTIONAL



MO.I.ME. Di Molè G. & C. s.a.s. C.da Coffa - Zona PIP - 97012 Chiaramonte Gulfi (Rg)
tel. fax +39 0932 922294 e:mail info@moime.it www.moime.it
P.I.V.A. C.F. IT 00878250885

Carpenteria Metallica - Serbatoi Gasolio - Silos
Strutture metalliche marcate CE
secondo Uni EN 1090-1:2009+A1:2011

UNI EN ISO 9001:2015

